

MANUFACTURER

OMI VINYL (ANHUI) Co., Ltd.
Address: Economic Development Langxi Anhui, CHINA
Tel: +86-563-7375880 Fax: +86-563-7373880
Web: www.omivinyl.com

PRODUCT DESCRIPTION

Yorktown ESPC is designed for use in commercial and residential applications. The Yorktown ESPC collection features a natural wood look. Its rugged construction, including a 6 mil wear layer topped with UV cured ceramic finish permits maximum durability ensuring long lasting beauty without the use of a floor finish. The composition ensures a 100% Virgin PVC and Phthalates Free with SPC Core. With excellent resistance to abrasion, chipping, cracking, and permanent indentations for heavy-duty performance requirements and to help conceal most substrate irregularities. Yorktown ESPC is the perfect choice for basements, homes, office buildings, banks, healthcare and condominiums, or wherever both function and high design are essential. The surface includes a micro bevel embossed surface to enhance the unique texture of wood, while adding slip resistance qualities to the plank. Precision cutting allows for easy 2G Click installation with tight seams.

AVAILABLE STYLES (ALL DIMENSIONS NOMINAL)

Thickness: Overall 5mm, 4mm + 1mm EVA Padding
Size: 7.09" x 48"
Packaging: 12 pieces per carton (28.36 sq. /ft. per Carton)
Pallet: 50 cartons, 16 pallets on container

TECHNICAL DATA

Product Classification

ASTM F 1700 - Solid Vinyl Tile; Class III, Type B

Fire Testing Information

ASTM E 648, Critical Radiant Flux - meet or exceeds Class 1

General Performance Information

ASTM C1028-96, Static Coefficient of Friction .060
slip resistance Passes ADA/OSHA standard -

ASTM F970, Static Load - .004 inch Passes 250

ASTM F925, Resistance to Chemicals - No Change

ASTM F1514, Heat Stability of Color - $\Delta E < 8$ Avg

ASTM F1515, Light Stability of Color - $\Delta E < 8$ Avg

ASTM F1914, Residual Indentation - 3.4%

ASTM F2199, Dimensional Stability -.20" / in ft

ASTM E648 Critical Radiant Flux Class 1

ASTM E492-09 Impact Sound Conduction IIC 64db

ASTM E90-09 Airborne Sound Conduction STC 64db

ASTM F2753 Rolling load over Resilient .024 inch

PSI: 5000lb

TECHNICAL ASSISTANCE

Please contact your local rep or call 336-781-3816


WARRANTY

Lifetime Manufacturer's Warranty


Lifetime Waterproof Warranty

Limited Fifteen (15) Year Commercial Wear Warranty

Lifetime Year Residential Wear Warranty




BARN OAK ESPC44112C




CATALINA ESPC44103C




CLASSIC OAK ESPC44193C




COLONIAL OAK ESPC44101C




ENGLISH OAK ESPC44173C



LIBERTY OAK ESPC44168C




RUSTIC OAK ESPC44154C




RUSTIC WALNUT ESPC44191C




TAVERN OAK ESPC44105C



TOFFEE OAK ESPC44123C



TORREY PINE ESPC44102C



VIRGINIA PINE ESPC44185C